

Drivol SUPERBOAT 2T

Outboard Motor Oil

SUPERBOAT 2T

Product Description:

Drivol Super boat 2T oil is a premium-grade lubricant designed for two-stroke outboard engines, offering exceptional performance in both water-cooled and air-cooled environments. Crafted with a balanced combination of refined base oil with high flash point aromatic solvent and ashless additive package, effectively inhibits deposit formation, pre-ignition, and spark plug fouling. It delivers superior lubrication and effective control of deposits across various application.

Key Features:

- Resist & minimize the risk of harmful pre ignition.
- Outstanding corrosion and rust protection, enhanced engine life.
- Reduced spark plug fouling under a wide range of operating conditions.
- Safeguarding against wear under high-speed, high-performance operation.
- Protection against ring sticking maintaining combustion efficiency & power output.

Applications:

- Suitable for Water-cooled, two-stroke, marine outboard motors, jet skis and personal watercrafts.
- Recommended for air cooled, 2 stroke engines where a TC-W3 oil is specified.

Specification / Recommendations:

International Standards & Meet the Requirements	
API TD/ NMMA TC-W3	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.864
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	52.6
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	8.73
5	Viscosity Index	ASTM D2270	144
6	Flash Point COC (°C)	ASTM D92	110
7	Pour Point (°C)	ASTM D97	-36

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

