

Drivol Maxpro Plus Transmission Fluids & Gear Oils SAE 75W-80 GL-5

Product Description:

Drivol Maxpro Plus SAE 75W-80 GL-5 stands as a premium fully synthetic multigrade gear and transmission oil, blended from top-tier synthetic base oils. It integrates precisely balanced extreme pressure additives, engineered to mitigate scuffing and scoring encountered by transmission gears operating under high-speed, high-torque conditions.

Key Features:

- Prolonged oil drain intervals
- Robust wear protection for gears and bearings
- Exceptional low-temperature flow characteristics
- Elevated levels of shear stability and viscosity retention
- Remarkable fuel efficiency and reduced oil consumption

Applications:

- Specifically formulated for hypoid differentials, axles, and final drives necessitating API GL-5 SAE 75W-80 gear lubricants.
- Suited for a broad spectrum of vehicles including passenger cars, SUVs, light trucks, heavy commercial vehicles, and off-road equipment.

Specification / Recommendations:

International Standards & Meet the Requirements	
GL-5/ MIL L 2105 C; FORD WSD M2C200-C, MACK GO-J PLUS; PSA B71 2330	

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.864
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	56.8
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	9.5
5	Viscosity Index	ASTM D2270	151
6	Flash Point COC (°C)	ASTM D92	218
7	Pour Point (°C)	ASTM D97	-42

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

