



Drivol Maxpro Plus Transmission Fluids & Gear Oils SAE 75W-90 GL-5

Product Description:

Drivol Maxpro Plus SAE 75W-90 GL-5 embodies a fully synthetic gear lubricant engineered to cater year-round usage, formulated from synthetic base oils and an advanced additive ensemble to meet the rigorous demands of both light and heavy-duty commercial vehicles. It delivers outstanding fluidity even in frigid temperatures, ensuring reliable lubrication during transmission and transaxle startup in extremely cold conditions. Furthermore, it maintains a durable protective oil film even in exceedingly hot operational environments.

Key Features:

- · Enhanced frictional properties
- Dependable extreme pressure shielding
- Resilience against high-temperature oxidation
- Outstanding defense against wear under low-speed, high-torque conditions
- Extended-drain capability aids in reducing overhaul and maintenance downtime

Applications:

• Recommended for powered transmission and axle drives in automobiles, highway light and heavy-duty trucks, buses, and vans where API GL-5 compliance is mandatory.

Specification / Recommendations:

International Standards & Meet the Requirements

GL-5/ MACK GO-J PLUS; MAN 342 Type M1; MAN 342 Type 2, MAN 342 Type 3, SCANIA STO 1:0

Technical Data:

| S. No. | Characteristics | Test Method | Test Results |
|--------|-----------------------------------|-------------|----------------|
| 1 | Appearance | Visual | Bright & Clear |
| 2 | Density @ 15°C (g/ml) | ASTM D1298 | 0.869 |
| 3 | Kinematic Viscosity @ 40°C (cSt) | ASTM D445 | 101 |
| 4 | Kinematic Viscosity @ 100°C (cSt) | ASTM D445 | 15.2 |
| 5 | Viscosity Index | ASTM D2270 | 159 |
| 6 | Flash Point COC (°C) | ASTM D92 | 206 |
| 7 | Pour Point (°C) | ASTM D97 | -42 |

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.



