

Drivol Maxpro

Transmission Fluids & Gear Oils

SAE 85W-140 GL-5

Product Description:

Drivol Maxpro SAE 85W-140 GL-5 is a premium multigrade automotive gear oil formulated with mineral base stocks and fortified with extreme pressure additives, provides excellent protection to gears and other components even under heavy duty conditions. Its sophisticated formulation shields gear surfaces from wear, while specialized molecules guarantee uniform lubrication, ultimately leading to improved durability and a seamless driving experience.

Key Features:

- Minimal deposits for extended gear and bearing lifespan.
- Enhanced longevity with reduced wear, prolonging component life.
- Rapid oil circulation during cold start-up facilitated by low temperature fluidity.
- Reliable protection against scuffing and wear for critical components with EP additives.

Applications:

- Recommended for gear boxes and axles meeting API GL-5 standards and requiring SAE 85W-140 viscosity.
- Ideal for automotive hypoid drive axles, steering systems, non-synchronized transmissions, and transaxles.

Specification / Recommendations:

International Standards & Meet the Requirements	
	GL-5

Technical Data:

S. No.	Characteristics	Test Method	Test Results
1	Appearance	Visual	Bright & Clear
2	Density @ 15°C (g/ml)	ASTM D1298	0.908
3	Kinematic Viscosity @ 40°C (cSt)	ASTM D445	345
4	Kinematic Viscosity @ 100°C (cSt)	ASTM D445	26.4
5	Viscosity Index	ASTM D2270	101
6	Flash Point COC (°C)	ASTM D92	220
7	Pour Point (°C)	ASTM D97	-18

Manufacturing:

Manufactured in ISO 9001: 2015 and ISO 14001:2015 certified plant.

Disposal:

Environment protection to be ascertained by proper disposal of Used oil and empty container as per local country guidelines.

